

# Type: BHRM

## Hours Run Meter

- ❑ Non Resettable
- ❑ Measures Elapsed Time
- ❑ Rotating Disc for Indication of Operation
- ❑ Panel Mounting
- ❑ IP65 Protection (Front Face)



### • INSTALLATION NOTE



Installation work must be carried out by qualified personnel.

- BEFORE INSTALLATION, ISOLATE THE SUPPLY.

### • TECHNICAL SPECIFICATION

Supply voltage:	10 – 80V DC 24, 115, 230V AC 50Hz	Please state Supply voltage when ordering.
Supply voltage tolerance:	+/-10% (AC Supply versions)	
Current consumption:	DC: 1.5 - 15mA (at rated supply voltage) AC: ≈10mA	
Counting capacity:	99,999.99 Hours	
Ambient temp:	-30 to + 80°C	
Protection:	DIN 40050, housing IP65 (front)	
Weight:	= 46g	
Mounting:	Flush, Panel cut-out options	
	1. 45.2mm + 0.3 (See Fig.1) 2. Ø 50.2mm + 0.3 (See Fig.2)	
Terminations:	Terminal screw connection	
Approvals:	CE Compliant.	

### • DIMENSIONS & PANEL CUT-OUT DETAILS

