

NEW

BROYCE
CONTROL

Passionate about protection and control



C  US LISTED

Timers

Timers

LMMT

Multifunction

- 7 Selectable functions
- 7 Selectable time ranges (0.1 seconds – 100 hours)
- Fine adjustment of selected time range
- Multi-voltage input (12 – 230V AC/DC +/-15%)
- LED Warning indication if function is changed whilst powered
- 1 x SPDT relay output 8A
- Green LED indication for supply / timing status
- Red LED indication for relay status
- Conforms to IEC 61812



C  US LISTED

Dims: to DIN 43880
W. 17.5mm

LMMT/2

Multifunction

- 7 Selectable functions
- 7 Selectable time ranges (0.1 seconds – 100 hours)
- Fine adjustment of selected time range
- Multi-voltage input (12 – 230V AC/DC +/-15%)
- LED Warning indication if function is changed whilst powered
- 1 x DPDT relay output 8A
- Green LED indication for supply / timing status
- Red LED indication for relay status
- Conforms to IEC 61812



C  US LISTED

Dims: to DIN 43880
W. 17.5mm

LEDO

Delay On Operate

- Supply initiated, Delay On Operate timing function
- 7 Selectable time ranges (0.1 seconds – 100 hours)
- Fine adjustment of selected time range
- Multi-voltage input (12 – 230V AC/DC +/-15%)
- 1 x SPDT relay output 8A
- Green LED indication for supply / timing status
- Red LED indication for relay status
- Conforms to IEC 61812



C  US LISTED

Dims: to DIN 43880
W. 17.5mm

LEDO/2

Delay On Operate

- Supply initiated, Delay On Operate timing function
- 7 Selectable time ranges (0.1 seconds – 100 hours)
- Fine adjustment of selected time range
- Multi-voltage input (12 – 230V AC/DC +/-15%)
- 1 x DPDT relay output 8A
- Green LED indication for supply / timing status
- Red LED indication for relay status
- Conforms to IEC 61812



C  US LISTED

NEW

Dims: to DIN 43880
W. 17.5mm

Timers

LART

Asymmetrical Recycling

- Recycling "On / Off" function **AN** ("Off / On" **AF** when external link fitted)
- Separate adjustments for "on" and "off" ranges
- 7 Selectable time ranges (0.1 seconds – 100 hours)
- Fine adjustment of selected time range
- Multi-voltage input (12 – 230V AC/DC +/-15%)
- 1 x SPDT relay output 8A
- Green LED indication for supply / timing status
- Red LED indication for relay status
- Conforms to IEC 61812



Dims: to DIN 43880
W. 17.5mm

LRTM/2

Delayed Pulse

- Recycling "Off / On" function **AF** ("Delayed Pulse" **DP** when external link fitted)
- Separate adjustments for "on" and "off" ranges
- 7 Selectable time ranges (0.1 seconds – 100 hours)
- Fine adjustment of selected time range
- Multi-voltage input (12 – 230V AC/DC +/-15/-10%)
- 1 x DPDT relay output 8A
- Green LED indication for supply / timing status
- Red LED indication for relay status
- Conforms to IEC 61812



Dims: to DIN 43880
W. 17.5mm

LEIN

Interval

- Supply initiated, Interval timing function
- 7 Selectable time ranges (0.1 seconds – 100 hours)
- Fine adjustment of selected time range
- Multi-voltage input (12 – 230V AC/DC +/-15%)
- 1 x SPDT relay output 8A
- Green LED indication for supply / timing status
- Red LED indication for relay status
- Conforms to IEC 61812



Dims: to DIN 43880
W. 17.5mm

LESW

Switch Initiated Delay Off

- Switch initiated (Constant supply), Delay Off timing function
- 7 Selectable time ranges (0.1 seconds – 100 hours)
- Fine adjustment of selected time range
- Multi-voltage input (12 – 230V AC/DC +/-15%)
- 1 x SPDT relay output 8A
- Green LED indication for supply / timing status
- Red LED indication for relay status
- Conforms to IEC 61812



Dims: to DIN 43880
W. 17.5mm

Timers



LEDF

True Delay Off

- True Delay Off timing function
- Adjustment of time delay range
- Choice of 4 time ranges (0.5 - 10s, 1 - 30s, 2 - 60s or 0.5 - 10m)
- Dual-voltage input (24V AC/DC // 110V AC or 24V AC/DC // 230V AC)
- 1 x SPDT relay output 8A
- Green LED indication for supply status



Dims: to DIN 43880
W. 17.5mm



LEYD/A

Star / Delta

- Star / Delta Start timing function
- 7 Selectable time ranges (0.1 seconds – 100 hours)
- Fine adjustment of selected time range
- Selectable "Dwell" time (40 - 160ms)
- Multi-voltage input (12 – 230V AC/DC +15/-10%)
- 1 x SPDT relay output 6A
- Green LED indication for supply / timing status
- Red LED indication for relay status
- Conforms to IEC 61812



Dims: to DIN 43880
W. 17.5mm



LEDK

Delay On Operate with Instantaneous Contact

- Delay On Operate with Instantaneous Contact timing function
- 7 Selectable time ranges (0.1 seconds – 100 hours)
- Fine adjustment of selected time range
- Multi-voltage input (12 – 230V AC/DC +15/-10%)
- 2 x SPDT relay outputs 8A
- Green LED indication for supply / timing status
- Red LED indication for relay status
- Conforms to IEC 61812



Dims: to DIN 43880
W. 17.5mm



LMAT

Multi-Attempt to Start

- Multi-Attempt to Start timing function
- Separate adjustments for "on" and "off" time ranges
- 7 Selectable "Start Attempts" (2 - 8)
- Multi-voltage input (12 – 48V AC/DC +10/-30%)
- 2 x SPDT relay outputs 8A
- Green LED indication for supply / timing status
- Red LED indication for relay status
- Conforms to IEC 61812



Dims: to DIN 43880
W. 17.5mm



NOTE: Many other versions and options available which can be customised to suit your requirements!



Broyce Control Ltd. Pool Street, Wolverhampton,
West Midlands, WV2 4HN. U.K.
Tel: +44 (0) 1902 773746 Fax: +44 (0) 1902 420639
Email: sales@broycecontrol.com Web: www.broycecontrol.com



ISO 9001:2015
Cert. No. 14125771